

Product-/datasheet BambusPlank™

Technical service

Manufacturer	Holse & Wibroe A/S
Vat no.	CVR-nr. 28281439
Address	Agenavej 16, 2670 Greve
Phone	+45 88 18 28 00
E-mail	Info@holseogwibroe.dk
Web-address	www.holseogwibroe.dk

Specifications

Item numbers	105102, 105202, 105302, 105602
Thickness	19,2 mm, $\pm 0,2$ mm
Width	150 mm, $\pm 0,2$ mm
Length	1900 mm, $\pm 0,5$ mm
Density	Approx. 680 kg/ Cbm
Reaction to fire	C _{fi} -s1 – (EN 13501-1:2018 with clause 12.5 & 12.9)
Emission of formaldehyde	E1
Thermal conductivity	0,17 W/mK
Durability	Class 1
Package content	2,28 sqm.
Weight/Package	Approx. 27 kg
Construction	Solid
Mechanic	Tongue & groove
Bevel	Micro

Surface

Lacquer	Lacquered 5 times with Bona UV- matt lacquer (Natural or White). Gloss 6-8. Minor repairs before lacquer may occur.
Oil	Treated 3 times with WOCA hardening oil (Natural or White). Before usage the surface should be treated with one time WOCA maintenance oil.

Installation & Maintenance

Installation	Installed on joists, floating or as fully glued. Always check latest updated version at www.holseogwibroe.dk
Maintenance & Care	check instruction at www.holseogwibroe.dk

July 2023