

## Product-/datasheet Bambus Ekstrem™ Click

### Technical service

Manufacturer	Holse & Wibroe A/S
Vat no.	CVR-nr. 28281439
Address	Agenavej 16, 2670 Greve
Phone	+45 88 18 28 00
E-mail	<a href="mailto:Info@holseogwibroe.dk">Info@holseogwibroe.dk</a>
Web-address	<a href="http://www.holseogwibroe.dk">www.holseogwibroe.dk</a>

### Specifications

Item numbers	110208, 110408, 110608, 115208, 115408
Thickness	14 mm, ±0,20 mm
Width	135 mm, ±0,20 mm
Length	1830 mm, ±0,50 mm
Density	Approx. 1.050 kg/ Cbm
Reaction to fire	C <sub>fi</sub> -s1 – (EN 13501-1:2018 with clause 12.5 & 12.9)
Emission of formaldehyde	E1
Thermal conductivity	0,24 W/mK
Durability	Class 1
Package content	1,98 sqm.
Weight/Package	Approx 29 Kg.
Construction	Solid
Mechanic	Click 4 sides.
Bevel	Micro

### Surface treatment

Lacquer	Lacquered 5 times with BONA-UV matt lacquer (Natural or White). Gloss 6-8 Minor repairs before lacquer may occur.
Oil	Treated 3 times with WOCA hardening natural oil. Smaller cracks may occur in the surface due to the compression.  Before usage, the surface should be sanded with the supplied "Net 180" and then oiled 1 time with WOCA maintenance oil.

## Installation & Maintenance

Installation	To be installed floating. Always check latest updated version at <a href="http://www.holseogwibroe.dk">www.holseogwibroe.dk</a>
Maintenance & Care	Check latest version at <a href="http://www.holseogwibroe.dk">www.holseogwibroe.dk</a>

July 2023