

## Product-/datasheet Bambus Ekstrem LamelPlank™

### Technical service

Manufacturer	Holse & Wibroe A/S
Vat no.	CVR-nr. 28281439
Address	Agenavej 16, 2670 Greve
Phone	+45 88 18 28 00
E-mail	<a href="mailto:Info@holseogwibroe.dk">Info@holseogwibroe.dk</a>
Web-address	<a href="http://www.holseogwibroe.dk">www.holseogwibroe.dk</a>

### Specifications

Item numbers	130407, 130607, 135407
Thickness	22 mm, ±0,20 mm
Width	192 mm, ±0,20 mm
Length	1830 mm, ±0,50 mm
Density	Top layer approx. 1.050 kg/ CBM. Total approx. 600kg.
Reaction to fire	C <sub>fi</sub> -s1 – (EN 13501-1:2018 with clause 12.5 & 12.9)
Emission of formaldehyde	E1
Thermal conductivity	0,17 W/mK
Durability	Class 1
Package content	2,11 sqm.
Weight/Package	Approx 33 Kg.
Construction	3 mm Bambus Ekstrem Top layer -installed on 19 mm multiplywood-core.
Mechanic	Tongue & groove
Bevel	Micro

### Surface treatment

Lacquer	Lacquered 5 times with Bona UV matt lacquer (Natural or White). Gloss 6-8. Minor repairs before lacquer may occur.
Oil	Treated 3 times with WOCA hardening natural oil. Smaller cracks may occur in the surface due to the compression. Before usage, the surface should be sanded with the supplied "Net 180" and then treated one time with WOCA maintenance oil.

## Installation & Maintenance

Installation	Installed on joists, floating or as fully glued. Always check latest updated version at <a href="http://www.holseogwibroe.dk">www.holseogwibroe.dk</a>
Maintenance & Care	Check latest version at <a href="http://www.holseogwibroe.dk">www.holseogwibroe.dk</a>

July 2023